



FUNCTION TABLE:

NO.	SYMBOL	NO.	SYMBOL
27	DB2	34	/CS1
26	DB3	33	/RES
25	DB4	32	A0
24	DB5	31	/WR (W/R)
23	DB6 (SCL)	30	/RD (E)
22	DB7 (SCI)	29	DB0
21	VDD	28	DB1
20	VSS		
19	VOUT		
18	C5+		
17	C3+		
16	C1-		
15	C1+		
14	C2+		
13	C2-		
12	C4+		
11	VRS		
10	V4		
9	V3		
8	V2		
7	V1		
6	V0		
5	VR		
4	C86		
3	P/S		
2	/HPM		
1	IRS		

OPERATING VOLTAGE: 3.3V	OPERATING CURRENT: 1.0mA MAX
DISPLAY TYPE: SIM-V/G, POSITIVE	POLARIZER MODE: TRANSPARENT
LCD DRIVE METHOD: 1/65DUTY 1/9BIAS 9.0V	VIEW DIRECTION: 6:00 O'CLOCK
LCD DRIVER IC: ST7565P	BACK LIGHT: --
OPERATING TEMPERATURE: -20°C TO 70°C	STORAGE TEMPERATURE: -30°C TO 80°C
DEFAULT TOLERANCE: ±0.2	ROHS STANDARD: YES

		SHARES LIMITED	
TITLE	模块外形图	CUSTOMER NUMBER	--
DES' D BY		PRODUCT MODEL	WM12864K4G
CHK' D BY		SERIAL NUMBER	
APPROVED		SCALE	1:1
		REV	A
		UNTT	mm
		DATE	2007-10-31
		NO.	1/1