


NOTE:

1. FSTN, POSITIVE, TRANSPARENT
2. 1/65 DUTY, 1/9BIAS, Vop.=10.0V
3. V.D:6:00
4. OP.TEMP:-20°C-70°C
5. ST.TEMP:-30°C-80°C
6. Driver IC: ST7565P
7. 背光电压: 3.0V



SCALE 10:1

|        |      |      |     |        |       |     |      |     |     |
|--------|------|------|-----|--------|-------|-----|------|-----|-----|
| PIN    | 1    | 2    | 3   | 4      | 5     | 6   | 7    | 8   | 9   |
| SYMBOL | /CS1 | /RES | AO  | WR(RW) | RD(E) | D0  | D1   | D2  | D3  |
| PIN    | 10   | 11   | 12  | 13     | 14    | 15  | 16   | 17  | 18  |
| SYMBOL | D4   | D5   | D6  | D7     | VDD   | VSS | VOUT | C5- | C3- |
| PIN    | 19   | 20   | 21  | 22     | 23    | 24  | 25   | 26  | 27  |
| SYMBOL | C1+  | C1-  | C2- | C2+    | C4-   | VRS | V1   | V2  | V3  |
| PIN    | 28   | 29   | 30  | 31     | 32    | 33  | 34   |     |     |
| SYMBOL | V4   | V5   | VR  | C86    | P/S   | HPM | IRS  |     |     |

| 更改记录 |    |      |    |    |    | 设计 | 审核       | 工艺 | 标准化 | 批准 | 产品型号 | WYM12864K1G |
|------|----|------|----|----|----|----|----------|----|-----|----|------|-------------|
| 更改标记 | 日期 | 更改内容 | 设计 | 审核 | 批准 | 签名 | 赵强       |    |     |    | 部件编号 | WYM12864K1G |
|      |    |      |    |    |    | 日期 | 08.07.11 |    |     |    | 分文件号 | 6           |
|      |    |      |    |    |    |    |          |    |     |    | 页数   | 1-1 单位 mm   |