



1	VDD	Power supply (+3.3V)
2	VSS	Power ground
3	NC	No connection
4	/rd	Read signal
5	/wr	Write signal
6	A0	"H": Data ; "L": Instruction
7	/CS	Chip select
8	/RES	Reset signal
9	DB0	DATA BUS 0
10	DB1	DATA BUS 1
11	DB2	DATA BUS 2
12	DB3	DATA BUS 3
13	DB4	DATA BUS 4
14	DB5	DATA BUS 5
15	DB6	DATA BUS 6
16	DB7	DATA BUS 7
17	A	Backlight (+) +3.3V
18	K	Backlight (-)

NOTES:

1. DISPLAY TYPE: FSTN
2. POLARIZER TYPE: TRANSPARENT, POSITIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +3.3V
7. DRIVE METHOD: 1/160DUTY, 1/12BIAS
8. CONTROLLER: UC1698
9. BACKLIGHT TYPE: WHITE
10. BACKLIGHT SUPPLY VOLTAGE: +3.3V

WYING WAYING (HONGKONG) SHARES LIMITED

DESIGN: MODEL NUMBER: WYM240160D UNITS: MM

CHECK: VERSION: A

APPROVE: SHEET: 1 OF 1

Unspecified tolerances are ±0.3 DATE: 2012-05-18